

SPECIFICATION SHEET

TEHNIČKI LIST



COLLECTION
SERIJA

SMART

PRODUCT CODE
ŠIFRA PROIZVODA

JA331001



TEHNIČKI PODACI

Jednoručna baterija
Zidna montaža
Klasa protoka C -na izlivu
NEOPERL® PERLATOR® Coin Slot®
Keramički mešač KEROX® 35
Poluautomatski prebacivač za tuš
Polirane Inox 304 rozete
Heavy Duty ekscentar kolena
Duplo pleteno tuš crevo 1.5m
Easy Clean tuš ručica
Fiksni držač tuša

RADNI USLOVI

Maksimalni radni pritisak: 5 bar
Preporučeni radni pritisak: 3 bar
Minimalni radni pritisak: 1 bar
Maksimalna dozvoljena temperatura: 70°C
Preporučena temperatura vode: 50°C

TECHNICAL DETAILS

Single lever mixer
Attached to the wall
Flow rate C - on spout
NEOPERL® PERLATOR® Coin Slot®
Ceramic cartridge KEROX® 35
Semi-automatic shower diverter
Polished SS304 rosettes
Heavy Duty eccentrics
Double lock shower hose 1.5m
Easy Clean hand shower
Shower wall support

WORKING CONDITIONS

Max. working pressure : 5 bar
Suggested working pressure : 3 bar
Min. working pressure : 1 bar
Max. working temperature : 70°C
Suggested max. water temperature : 50°C

email : info@rosan.rs

www.rosan.rs

