

SPECIFICATION SHEET

TEHNIČKI LIST



COLLECTION
SERIJA

BRONTEE

PRODUCT CODE
ŠIFRA PROIZVODA

NB12101



TEHNIČKI PODACI

Dvoručna baterija
Zidna montaža
Flühs® LIFETIME keramički gornji delovi
Metalni rukohvat
Ručni prebacivač
Specijalna Brontee završna obrad
Duplo pleteno tuš crevo 1.5m
Metalna tuš ručica
Heavy Duty ekscentar kolena

RADNI USLOVI

Maksimalni radni pritisak: 5 bar
Preporučeni radni pritisak: 3 bar
Minimalni radni pritisak: 1 bar
Maksimalna dozvoljena temperatura: 70°C
Preporučena temperatura vode: 50°C

email : info@rosan.rs

www.rosan.rs

TECHNICAL DETAILS

Two handle mixer
Wall mounted
Flühs® LIFETIME ceramic head parts
Metal handle
Manual diverter
Special Brontee finish
Double lock shower hose 1.5m
Solid brass hand shower
Heavy Duty eccentric connectors

WORKING CONDITIONS

Max. working pressure : 5 bar
Suggested working pressure : 3 bar
Min. working pressure : 1 bar
Max. working temperature : 70°C
Suggested max. water temperature : 50°C

